DATA MODUL

CONRAC PROFESSIONAL DISPLAYS – Real Outdoor – D-LED – 16:9 format

55"/139 cm 7955 PD

Display

Active screen dimensions (h x v) 1209.6 x 680.4 mm

Resolution (pixel) 1920 x 1080

Viewing angle (typical) 178°

Contrast ratio (typical) 1300:1

Brightness 4500 cd/m² (panel typ.)
Color performance 16.7 million colors
Backlight system D-LED (Direct LED)

Optical enhancement Direct optical bonding of antireflective coated front glass to TFT panel.

Impact resistance IKOS

Environmental conditions

IP protection IP 65
Temperature (operating) -33° C to +50° C
Temperature (non-operating) -20° C to +60° C
Humidity 10% to 100%

Power

Power supply 90V to 264V, 47Hz to 63Hz
Power consumption (depending on configuration)
With integrated PC 300W typical
Heating / Cooling active (max.) 850W

Dimensions & Weight

H x W x D 758 x 1287 x 193 mm Weight (+/- 5%) 95 kg

Approvals

 EMI/EMC
 EN55022 class A, EN55024, EN61000-3-2/-3

 Safety
 EN60950, CE

Colour

Standard colour cabinet RAL 9005 (black), powder coated

